

JD / AD SERIES / Architectural Point Light

AD11

Architectural Point Light

High-output 24V architectural point light for larger-pixel facade applications, with RGB, RGBW and white configurations, DMX512/ON-OFF control, bracket or screw mounting and IP67 protection.

VOLTAGE 24V	POWER 5.0W / 8.0W / 10.0W	CONTROL DMX512 / ON/OFF	OUTPUT RGB / RGBW / White
IP RATING IP67	BEAM OPTIONS 110 deg	DIMENSIONS 133.9 x 112 x 50 mm	REFERENCE AD series

Mechanical and optical summary

LED / LIGHT SOURCE	3535 RGB x 24; RGBW version adds 2835 White x 12; white versions use 2835 White x 24.
CABLE / CONNECTOR	DMX versions: 2 x 1.0 mm2 power + 3 x 0.3 mm2 signal; ON/OFF white version: 2 x 1.0 mm2.
CCT OPTIONS	2200K / 2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K

Project configuration

Select voltage, output, control protocol, optical option, cable and mounting according to the approved project submittal. Do not mix variants without confirming the system design.

Configuration matrix

OUTPUT	VOLTAGE	POWER	CONTROL
RGB	24V	5W	DMX512
RGBW	24V	8W	DMX512
White	24V	10W	DMX512
White	24V	10W	ON/OFF

Specification notes

CCT OPTIONS	2200K / 2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K
BEAM OPTIONS	110 deg
DIMENSIONS	133.9 x 112 x 50 mm
LED / LIGHT SOURCE	3535 RGB x 24; RGBW version adds 2835 White x 12; white versions use 2835 White x 24.
CABLE / CONNECTOR	DMX versions: 2 x 1.0 mm ² power + 3 x 0.3 mm ² signal; ON/OFF white version: 2 x 1.0 mm ² .

Release boundary

Values shown are current structured product data. Final project wiring, connector, mounting, controller compatibility and released specifications must follow the selected variant and approved submittal.