

JD / AD SERIES / Architectural Point Light

AD14

Architectural Point Light

High-brightness 48V RGB architectural point light for large-pixel and daytime media-display applications, with 5.5W output, SPI control, 100 deg beam, IK07 impact resistance and IP66 protection.

VOLTAGE 48V	POWER 5.5W	CONTROL SPI	OUTPUT RGB
IP RATING IP66	BEAM OPTIONS 100 deg	DIMENSIONS Dia.62 x 32.5 mm	REFERENCE AD series

Mechanical and optical summary

LED / LIGHT SOURCE	3535 RGB x 24 (Lumileds platform).
CABLE / CONNECTOR	2 x 1.2 mm2 power + 2 x 0.3 mm2 SPI signal wiring.
CCT OPTIONS	Not applicable

Project configuration

Select voltage, output, control protocol, optical option, cable and mounting according to the approved project submittal. Do not mix variants without confirming the system design.

Configuration matrix

OUTPUT	VOLTAGE	POWER	CONTROL
RGB	48V	5.5W	SPI

Specification notes

CCT OPTIONS Not applicable

BEAM OPTIONS 100 deg

DIMENSIONS Dia.62 x 32.5 mm

LED / LIGHT SOURCE 3535 RGB x 24 (Lumileds platform).

CABLE / CONNECTOR 2 x 1.2 mm² power + 2 x 0.3 mm² SPI signal wiring.

Release boundary

Values shown are current structured product data. Final project wiring, connector, mounting, controller compatibility and released specifications must follow the selected variant and approved submittal.