

JD / AD SERIES / Architectural Point Light

JD15

Architectural Point Light

Compact 24V pixel point light for narrow facade details and profile-based installations, with RGB, RGBW and white options, DMX512/ON-OFF control, 120 deg optics and IP67 protection.

VOLTAGE 24V	POWER 1.0W / 1.5W	CONTROL DMX512 / ON/OFF	OUTPUT RGB / RGBW / White
IP RATING IP67	BEAM OPTIONS 120 deg	DIMENSIONS 70 x 23 x 15 mm	REFERENCE JD series

Mechanical and optical summary

LED / LIGHT SOURCE	3535 RGB x 4; RGBW version adds 2835 White x 2; white version uses 2835 White x 4.
CABLE / CONNECTOR	DMX versions: 2 x 0.75 mm2 power + 3 x 0.3 mm2 signal; ON/OFF white version: 2 x 0.75 mm2.
CCT OPTIONS	2200K / 2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K

Project configuration

Select voltage, output, control protocol, optical option, cable and mounting according to the approved project submittal. Do not mix variants without confirming the system design.

Configuration matrix

OUTPUT	VOLTAGE	POWER	CONTROL
RGB	24V	1W	DMX512
RGBW	24V	1.5W	DMX512
White	24V	1W	DMX512
White	24V	1W	ON/OFF

Specification notes

CCT OPTIONS	2200K / 2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K
BEAM OPTIONS	120 deg
DIMENSIONS	70 x 23 x 15 mm
LED / LIGHT SOURCE	3535 RGB x 4; RGBW version adds 2835 White x 2; white version uses 2835 White x 4.
CABLE / CONNECTOR	DMX versions: 2 x 0.75 mm ² power + 3 x 0.3 mm ² signal; ON/OFF white version: 2 x 0.75 mm ² .

Release boundary

Values shown are current structured product data. Final project wiring, connector, mounting, controller compatibility and released specifications must follow the selected variant and approved submittal.