

JD / AD SERIES / Architectural Point Light

JD34

Architectural Point Light

Architectural pixel point light for facade media and outline applications, available in 24V and 48V RGB/RGBW configurations with DMX512 control, standard 6-lights-per-meter spacing and IP67 protection.

VOLTAGE 24V / 48V	POWER 1.8W / 2.0W / 3.0W	CONTROL DMX512	OUTPUT RGB / RGBW
IP RATING IP67	BEAM OPTIONS 110 deg	DIMENSIONS 56 x 41.5 x 14 mm	REFERENCE JD series

Mechanical and optical summary

LED / LIGHT SOURCE	3535 RGB x 8; RGBW versions add 2835 White x 2.
CABLE / CONNECTOR	2 x 0.75 mm2 power + 3 x 0.3 mm2 DMX signal wiring.
CCT OPTIONS	2200K / 2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K

Project configuration

Select voltage, output, control protocol, optical option, cable and mounting according to the approved project submittal. Do not mix variants without confirming the system design.

Configuration matrix

OUTPUT	VOLTAGE	POWER	CONTROL
RGB	24V	1.8W	DMX512
RGB	48V	2W	DMX512
RGBW	24V	3W	DMX512
RGBW	48V	3W	DMX512

Specification notes

CCT OPTIONS 2200K / 2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K

BEAM OPTIONS 110 deg

DIMENSIONS 56 x 41.5 x 14 mm

LED / LIGHT SOURCE 3535 RGB x 8; RGBW versions add 2835 White x 2.

CABLE / CONNECTOR 2 x 0.75 mm² power + 3 x 0.3 mm² DMX signal wiring.

Release boundary

Values shown are current structured product data. Final project wiring, connector, mounting, controller compatibility and released specifications must follow the selected variant and approved submittal.