

TG SERIES / Architectural Flood Light

TG17

Architectural Flood Light

Reference SKU: W220L

220V input, 120W RGBW output, DMX512 control, multiple optical options and IP65 protection.

VOLTAGE 220V	POWER 120W	CONTROL DMX512	LIGHT OUTPUT RGBW
IP RATING IP65	BEAM OPTIONS 20 deg / 30 deg / 45 deg / 60 deg / 20 x 55 deg	DIMENSIONS 220 x 120 x 290 mm	REFERENCE W220L

Mechanical and optical summary

DIMENSIONS	LED / LIGHT SOURCE
220 x 120 x 290 mm	Osram 3535 RGBW 4-in-1 x 48
CABLE / CONNECTOR	BEAM OPTIONS
AC power cable plus separate signal cable / project connector configuration	20 deg / 30 deg / 45 deg / 60 deg / 20 x 55 deg

Application reference

Architectural facade / landscape flood lighting

Use the selected beam, bracket, cable and control configuration in accordance with the approved project submittal. Final electrical loading, mounting and aiming must be confirmed for the actual project.

Configuration matrix

Output	Voltage	Power	Control	Protection
RGBW	220V	120W	DMX512	IP65

Optical and mechanical reference

BEAM OPTIONS	20 deg / 30 deg / 45 deg / 60 deg / 20 x 55 deg
DIMENSIONS	220 x 120 x 290 mm
LED / LIGHT SOURCE	Osram 3535 RGBW 4-in-1 x 48
CABLE / CONNECTOR	AC power cable plus separate signal cable / project connector configuration
REFERENCE SKU	W220L

Engineering notes

Reference product data is based on the current SHLED TG flood-light structured product record. Final voltage, power, beam angle, control, bracket and cable configuration must follow the selected model and released project submittal.

Project confirmation required

Final electrical load, optical selection, mounting, aiming, cable, connector and control details must match the approved project specification. Specifications may be refined as controlled documentation is consolidated.