

TG SERIES / Architectural Flood Light

Architectural Flood Light

TG20

Reference SKU: W465P

220V input, 240W RGBW output, DMX512 control, multiple optical options and IP65 protection.

VOLTAGE 220V	POWER 240W	CONTROL DMX512	LIGHT OUTPUT RGBW
IP RATING IP65	BEAM OPTIONS 8-60 deg / 20 x 40 deg / 20 x 55 deg	DIMENSIONS 490 x 352 x 129 mm	REFERENCE W465P

Mechanical and optical summary

DIMENSIONS	LED / LIGHT SOURCE
490 x 352 x 129 mm	3535 RGBW 4-in-1 x 72
CABLE / CONNECTOR	BEAM OPTIONS
AC power cable plus separate signal cable / project connector configuration	8-60 deg / 20 x 40 deg / 20 x 55 deg

Application reference

Architectural facade / landscape flood lighting

Use the selected beam, bracket, cable and control configuration in accordance with the approved project submittal. Final electrical loading, mounting and aiming must be confirmed for the actual project.

Configuration matrix

Output	Voltage	Power	Control	Protection
RGBW	220V	240W	DMX512	IP65

Optical and mechanical reference

BEAM OPTIONS	8-60 deg / 20 x 40 deg / 20 x 55 deg
DIMENSIONS	490 x 352 x 129 mm
LED / LIGHT SOURCE	3535 RGBW 4-in-1 x 72
CABLE / CONNECTOR	AC power cable plus separate signal cable / project connector configuration
REFERENCE SKU	W465P

Engineering notes

Reference product data is based on the current SHLED TG flood-light structured product record. Final voltage, power, beam angle, control, bracket and cable configuration must follow the selected model and released project submittal.

Project confirmation required

Final electrical load, optical selection, mounting, aiming, cable, connector and control details must match the approved project specification. Specifications may be refined as controlled documentation is consolidated.