

XQ SERIES / Architectural Wall Washer

Architectural Wall Washer

XQ06

Higher-output 24V architectural wall washer with multiple power levels, optics and glare-control options for larger facade surfaces.

VOLTAGE 24V	POWER OPTIONS 12W / 18W / 24W / 36W / 48W	CONTROL DMX512 / ON/OFF	LIGHT OUTPUT RGBW / White
IP RATING IP65	LENGTHS 300 mm / 500 mm / 1000 mm	BEAM / DISTRIBUTION 12° / 15° / 20° / 30° / 45° / 60° / 15x30° / 20x60°	CCT 4000K

Mechanical and optical summary

DIMENSIONS	LED / LIGHT SOURCE
300 / 500 / 1000 mm; 44.3 mm wide profile; optional glare shield	3030 RGBW / 3030 White
CABLE / CONNECTOR	BEAM OPTIONS
DMX: 2x1.0 mm2 + 3x0.3 mm2; ON/OFF white: 2x1.0 mm2	12° / 15° / 20° / 30° / 45° / 60° / 15x30° / 20x60°

Dimension summary - not to scale

Standard lengths 300 mm / 500 mm / 1000 mm	Profile / mechanical summary 300 / 500 / 1000 mm; 44.3 mm wide profile; optional glare shield
This summary does not replace the controlled mechanical drawing. Mounting bracket, hole spacing and cable-exit details must follow the approved project drawing.	

Configuration matrix

Length	Output	Voltage	Power	Control	Pixel segments
1000 mm	RGBW	24V	36W	DMX512	3
1000 mm	RGBW	24V	48W	DMX512	3
1000 mm	White	24V	36W	DMX512	1
1000 mm	White	24V	48W	DMX512	1
1000 mm	White	24V	36W	ON/OFF	-
1000 mm	White	24V	48W	ON/OFF	-
500 mm	RGBW	24V	18W	DMX512	1
500 mm	RGBW	24V	24W	DMX512	2
500 mm	White	24V	18W	DMX512	1
500 mm	White	24V	24W	DMX512	1
500 mm	White	24V	18W	ON/OFF	-
500 mm	White	24V	24W	ON/OFF	-
300 mm	RGBW	24V	12W	DMX512	1
300 mm	White	24V	12W	DMX512	1
300 mm	White	24V	12W	ON/OFF	-

Engineering notes

1000 mm and 500 mm versions include multiple power configurations. Confirm output and optics per project.

Project confirmation required

Final voltage, power, control, light output, optics, cable, connector and mounting details must match the approved project specification and order configuration. Specifications may be refined without notice as product documentation is consolidated.