

XT SERIES / Architectural Wall Washer

XT14

Architectural Wall Washer

Slim wall-wash linear platform with multiple mounting brackets and narrow/elliptical optics for close-to-facade integration.

VOLTAGE 24V	POWER OPTIONS 5.5W / 6W / 7.5W / 12W / 15W	CONTROL DMX512 / ON/OFF	LIGHT OUTPUT RGB / RGBW / White
IP RATING IP65	LENGTHS 300 mm / 500 mm / 1000 mm	BEAM / DISTRIBUTION 45° / 15x45°	CCT 4000K

Mechanical and optical summary

DIMENSIONS	LED / LIGHT SOURCE
300 / 500 / 1000 mm; 26.8 x 36 mm profile	5050 RGB / 5050 RGBW / 5050 or 2835 White
CABLE / CONNECTOR	BEAM OPTIONS
DMX: 2x0.75 mm2 + 3x0.3 mm2; constant white: 2x0.75 mm2	45° / 15x45°

Dimension summary - not to scale

Standard lengths 300 mm / 500 mm / 1000 mm	Profile / mechanical summary 300 / 500 / 1000 mm; 26.8 x 36 mm profile
This summary does not replace the controlled mechanical drawing. Mounting bracket, hole spacing and cable-exit details must follow the approved project drawing.	

Configuration matrix

Length	Output	Voltage	Power	Control	Pixel segments
1000 mm	RGB	24V	12W	DMX512	8
1000 mm	RGBW	24V	15W	DMX512	8
1000 mm	White	24V	12W	DMX512	8
1000 mm	White	24V	15W	ON/OFF	-
500 mm	RGB	24V	6W	DMX512	4
500 mm	RGBW	24V	7.5W	DMX512	4
500 mm	White	24V	6W	DMX512	4
500 mm	White	24V	7.5W	ON/OFF	-
300 mm	RGBW	24V	5.5W	DMX512	3

Engineering notes

Length, optics, RGB/RGBW/white output, control and bracket configuration should follow the selected variant.

Project confirmation required

Final voltage, power, control, light output, optics, cable, connector and mounting details must match the approved project specification and order configuration. Specifications may be refined without notice as product documentation is consolidated.