

XT SERIES / Architectural Linear Light

Architectural Linear Light

XT20

48V RGB architectural linear light designed for longer-run facade applications.

VOLTAGE 48V	POWER OPTIONS 2.5W / 5W / 10W	CONTROL DMX512	LIGHT OUTPUT RGB
IP RATING IP65	LENGTHS 250 mm / 500 mm / 1000 mm	BEAM / DISTRIBUTION 106° x 95°	CCT Not applicable / RGB only

Mechanical and optical summary

DIMENSIONS	LED / LIGHT SOURCE
1000 / 500 / 250 mm; 29.2 x 28.2 mm profile	5050 RGB
CABLE / CONNECTOR	BEAM OPTIONS
2x2.0 mm2 power + 3x0.25 mm2 DMX signal wiring	106° x 95°

Dimension summary - not to scale

Standard lengths 250 mm / 500 mm / 1000 mm	Profile / mechanical summary 1000 / 500 / 250 mm; 29.2 x 28.2 mm profile
This summary does not replace the controlled mechanical drawing. Mounting bracket, hole spacing and cable-exit details must follow the approved project drawing.	

Configuration matrix

Length	Output	Voltage	Power	Control	Pixel segments
1000 mm	RGB	48V	10W	DMX512	16
500 mm	RGB	48V	5W	DMX512	8
250 mm	RGB	48V	2.5W	DMX512	4

Engineering notes

Length, pixel-segment and 48V DMX configuration must be matched to the selected model variant.

Project confirmation required

Final voltage, power, control, light output, optics, cable, connector and mounting details must match the approved project specification and order configuration. Specifications may be refined without notice as product documentation is consolidated.