

XT SERIES / Architectural Linear Light

XT48

Architectural Linear Light

Architectural linear light with 110° distribution and RGB/RGBW/white options across three standard lengths.

VOLTAGE 24V	POWER OPTIONS 4.5W / 5.5W / 6W / 7.5W / 12W / 15W	CONTROL DMX512 / ON/OFF	LIGHT OUTPUT RGB / RGBW / White
IP RATING IP65	LENGTHS 300 mm / 500 mm / 1000 mm	BEAM / DISTRIBUTION 110°	CCT 2700K / 3000K / 4000K / 5000K / 5700K / 6500K

Mechanical and optical summary

DIMENSIONS	LED / LIGHT SOURCE
1000 / 500 / 300 mm; 27 x 50 mm profile	5050 RGB / RGBW / White
CABLE / CONNECTOR	BEAM OPTIONS
DMX: 2x0.75 mm ² power + 3x0.3 mm ² signal; white ON/OFF: 2x0.75 mm ² power	110°

Dimension summary - not to scale

Standard lengths

300 mm / 500 mm / 1000 mm

Profile / mechanical summary

1000 / 500 / 300 mm; 27 x 50 mm profile

This summary does not replace the controlled mechanical drawing. Mounting bracket, hole spacing and cable-exit details must follow the approved project drawing.

Configuration matrix

Length	Output	Voltage	Power	Control	Pixel segments
1000 mm	RGB	24V	12W	DMX512	8
1000 mm	RGBW	24V	15W		